



Concrete Pumps USA LLC

Tel: 435-615-0072

Email: [info@concretepumpsusa.com](mailto:info@concretepumpsusa.com)

Web: [www.concretepumpsusa.com](http://www.concretepumpsusa.com)

## Schwing Loop Belt Conveyor Features

**MORE REACH:** The Loop Belt outreaches all other truck mounted telescopic conveyors.

- ✓ LB40 reaches 129'9" from center of rotation. 72' vertical at 300
- ✓ LB33 reaches 108'0" from center of rotation. 60' vertical at 300

**MORE CAPACITY:** The 20" deep u-trough belts will allow you 40% more material delivery capacity and true large aggregate handling ability, but even more importantly, the wider belts can be run slower and cleaner.

**MORE RANGE:** Full 360 degree rotation with full 30 degrees up and 12 degrees down.

**POWERED SWING-OUT OUTRIGGERS:** Fully proportional, deploy quickly & easily without any manual effort. Machine is rock stable under full load.

**HIGH STRENGTH STEEL:** Boom and feeder are tubular welded construction which is stronger, lighter, & easier to repair and maintain.

**DUAL-DRIVE TELESCOPE:** Wire rope driver system is extremely powerful, very accessible, and allows all sections to move evenly

**TRANSFER:** Transition from feeder to boom designed for optimum capacity in all boom elevation configurations. Material transfers cleanly and without capacity reduction.

**CONTROLS:** Machine uses the latest technology for hydraulic and wireless control to assure smooth and reliable wireless control.

**SIMPLICITY:** Numerous design enhancements focused on ease of operation, easy maintenance and simplified repairs.

**PATENTED FEEDER DEPLOY SYSTEM:** Allows the operator to quickly and easily deploy the feed conveyor

**LOWEST OPERATING COSTS:** Because of the wider belts, more efficient transfers, and deep-trough U-rollers, the belts can be run slower, have much less cleanup, and use less fuel.

**Click to View Loop Belt Video:** <https://www.youtube.com/watch?v=IDL0-e9EqAU>